

- 1 -

AN ELECTRICAL CONNECTION DEVICE

Field of the Invention

The present invention broadly relates to an
5 electrical connection device for a machine cable.
Throughout this specification the term "machine cable" is
used for any machine, reeling or trailing cable that is
suitable to deliver power to mobile machinery such as
machinery in petroleum or mining industry. The term
10 "connector" is used for any plug, lug, electrical adaptor,
coupler or receptacle.

Background of the Invention

Machine cables are typically used to provide an
15 electrical connection for mobile electrical machines. For
example, in the mining or petroleum industry often large
electrical machinery is used and each machine cable may
have to provide power in the order of a few hundred
kilowatts to a few megawatts. Typically such power is
20 delivered with a voltage of one or more kilovolts. The
cables usually comprise a plurality of cores and are
connected using connectors including sockets and pins.

In an explosive environment, for example, particular
precaution must be taken and a flame path may be required
25 between the two connectors to reduce likelihood of
explosions. The flame path typically is formed between a
plug and a receptacle by positioning a cylindrical surface
that surrounds contacts and/or electrical leads of the
plug inside a respective cylindrical surface of the
30 receptacle. The mechanical tolerance between the
cylindrical surfaces is fine (typically 0.2 to 0.4mm). As
a consequence of the fine mechanical tolerance, canting or
seizing may occur which makes it difficult to engage or

- 2 -

disengage plug and receptacle.

It is known in the prior art to have a pawl and slot arrangement on a side of the plug and the receptacle which can be used to drive the plug and the receptacle together
5 to engage pins and sockets and the surfaces that form the flame path.

Summary of the Invention

The present invention provides in a first aspect an
10 electrical connection device for a machine cable, the device comprising:

a first connector having a first contact,
a second connector having a second contact, the first
connector and the second connector being moveable between
15 a disengaged condition in which the first and second contacts are remote from each other and an engaged condition in which the first and the second contacts are electrically connected and

a drive for imparting a driving force to drive the
20 first and the second connectors relative to each other whereby the first connector and the second connector move between the disengaged and the engaged positions, the drive being arranged to distribute the driving force around at least a portion of at least one of the first
25 and the second connectors.

Each of the first and the second connectors typically comprises a housing. The first and the second connectors typically also comprise first and second flame path
30 surfaces which are arranged so that one of the flame path surfaces surrounds the other flame path surface when the connectors are moved to the engaged position so as to define a flame path between the first and the second flame

- 3 -

path surfaces. The first and the second flame path surfaces are typically arranged so that, when the first and the second connectors are moved to the engaged position, the flame path surfaces mate with a tolerance of less than 0.4 mm, typically less than 0.2 mm between them.

In the prior art the pawl and slot arrangement applies driving force at one particular location only. Consequently, mechanical wedging, canting or seizing between the connectors, especially of the tightly mating metallic flame-path surfaces, may occur and often large forces are required to connect the connectors and mate the flame-path surfaces. In practice, these large forces may even bend one of the metallic bodies of the connectors. In the present invention, however, the drive force is distributed around at least a portion of the first and/or the second connector and the likelihood of wedging, canting or seizing between the first and the second connector therefore is reduced or even inhibited.

The drive typically has a first drive part associated with the first connector and a second drive part associated with the second connector. The first drive part and the second drive part may be arranged so that the driving force is distributed substantially equally around the first and/or the second connector. The first drive part typically comprises a ring-like element and the second connector typically comprises an engagement surface which extends at least in part around the second connector. The engagement surface typically surrounds the second connector entirely and the ring-like element typically surrounds in use the engagement surface entirely. The ring-like element and the engagement surface typically are arranged to engage with each other and to distribute the driving force substantially equally around

- 4 -

at least one of the first and the second connector.
Alternatively, the drive may be arranged to distribute the
drive force at discrete positions that at least in part
surround at least one of the first and the second

5 connector.

The first drive part and the second drive part
typically are arranged so that the first and the second
connectors can be driven relative to each other along a
substantially linear path.

10 For example, the drive may comprise a geared
arrangement. The geared arrangement of the drive may
comprise a threaded drive and a threaded portion. The
first drive part of the drive may be the threaded drive
and the second drive part may be the threaded portion.

15 The threaded portion of the geared arrangement
typically forms the engagement surface. The threaded
portion typically forms a part of the exterior surface of
the second connector. The threaded portion of the geared
arrangement may comprise a helical groove that is
20 positioned so that an imaginary axis about which the
helical groove is oriented is substantially parallel to
the movement of the first connector and the second
connector relative to each other.

For example, the ring-like element may be a toothed
25 wheel of the threaded drive and the threaded drive may
further comprise and a toothed shaft. The toothed wheel
typically has a toothed inner peripheral surface and a
toothed outer peripheral surface. The geared arrangement
may be arranged so that the toothed shaft engages with the
30 outer peripheral toothed surface of the ring-like toothed
wheel. The inner peripheral toothed surface of the ring-
like toothed wheel typically is arranged to engage with
the helical groove. The toothed shaft may be rotatable but

- 5 -

typically is captured in position relative to the first connector. The geared arrangement may be arranged so that a rotational motion of the toothed shaft is translated by the toothed wheel into a translational relative movement
5 of the connectors.

One of the first and the second connectors may have an elongated groove such as a keyway on its outer peripheral surface that is oriented along the imaginary axis. In this case the other connector may have a
10 projection such as a key that is arranged to slide in the elongated groove. The elongated groove and the projection may be arranged so that, in use, a rotation of the first connector relative to the second connector is avoided.

The first contact may be a pin and the second contact
15 may be a socket. Alternatively, the first contact may be a socket and the second contact may be a pin. The pin may also be one of a plurality of pins and the socket may be one of a plurality of sockets.

The electrical connection device typically is
20 suitable for delivery of a power of more than 100kW or even more than 1MW.

The present invention provides in a second aspect a method of connecting a first electrical connector with a
25 second electrical connector, the first electrical connector having a first contact and the second electrical connector having a second contact, the first connector and the second connector being moveable between a disengaged condition in which the first and second contact are remote
30 from each other and an engaged condition in which the first and second contacts are in electrical contact, the method comprising the steps of:

distributing a driving force around at least one of

- 6 -

the first and the second connectors and
driving the first and the second connector relative
to each other so that the first connector and the second
connector move between the disengaged and the engaged
5 position.

The present invention provides in a third aspect a
first electrical connector for a machine cable, the
connector comprising:

10 a first contact and
a drive part arranged for engagement with another drive
part of another connector that has a second contact in a
manner such that the first connector and the second
connector are moveable between a disengaged condition in
15 which the first and second contacts are remote from each
other and an engaged condition in which the first and
second contacts are in electrical contact

wherein in use at least one of the first and the
second drive parts imparts a driving force that is
20 distributed around at least one of the connectors.

The invention will be more fully understood from the
following description of specific embodiments of the
invention. The description is provided with reference to
25 the accompanying drawings.

Brief Description of the Drawings

Figure 1 shows a schematic representation (in part in
cross-section) of a connector according to a specific
30 embodiment of the invention,

Figure 2 shows a schematic cross-sectional
representation of a connector according to another
specific embodiment of the invention

- 7 -

Figure 3 shows a schematic cross-sectional representation of a connector according to further specific embodiment of the invention and

Figure 4 shows (a), (b) perspective views of toothed wheels, (c) a cross-sectional representation of a toothed shaft and (d) a perspective view of the toothed shaft according to embodiments of the invention.

Detailed Description of Specific Embodiments of the
10 Invention

Referring to Figures 1 to 4, an electrical connection device according to specific embodiments of the invention is now described. In this embodiment, the electrical connection device comprises connector 10 and connector 50 or connector 10 and connector 70.

In this embodiment components of the connectors 10, 50 and 70 are sized and structured so that the electrical connection device is suitable for delivery of a few hundred kW or a few MW of power. Connector 10 is arranged for connection to a multi-core machine cable such as a 3-phase cable having three multi-strand cores. Connector 50 is a back-to-back receptacle (restrained coupling device) arranged to connect two of the connectors 10. Connector 70 is a receptacle for connecting the connector 10 to a electrical machine.

Connector 10 is a plug that comprises an insulating body 11 which is of substantially cylindrical shape and an outer shell 12 composed of metallic and/or insulating polymeric material. The connector 10 has an end-face 13 that has three apertures (only two are shown in Figure 1) that are defined by nuts such as nuts 14 and 16. From each aperture an insulating sleeve 18 projects inwardly. The pin 20 is connected to a thimble 22 which is connected to

- 8 -

an individual core 24 of a multi-core machine cable 26. A further core 28 of the multi-core machine cable is also shown (not connected).

The outer shell 12 comprises a helical groove 34.
5 Figures 1 to 4 also show a ring-like toothed wheel 36 and a toothed shaft 38. The inner toothed surface 40 of toothed wheel 36 is arranged for engagement (meshing) with the helical groove 34 and the outer toothed surface 42 is arranged for engagement (meshing) with the toothed shaft
10 38.

Figure 2 shows a receptacle 50 comprising an outer shell 51. The outer shell 51 locates the toothed shaft 38 and the toothed wheel 36 so that the toothed wheel 36 is rotatable about an imaginary longitudinal central axis of
15 the receptacle 50 and the toothed shaft 38 is rotatable about a direction perpendicular to that. The receptacle 50 also comprises sockets 52 arranged for engagement with pins such as pin 20 shown in Figure 1. Pairs of the sockets 52 are electrically connected and held in position
20 by insulating body 53. The insulating body 53 also comprises earth connections 54.

The receptacle 70 shown in Figure 3 is related to that shown in Figure 2, but in this case comprises
thimbles 52a each arranged to receive an electrical
25 conductor (not shown) which in use are guided into the housing of an electrical machine (not shown). Flange 72 is arranged for mechanical connection to the housing of the electrical machine.

When the plug 10 is engaged with receptacles 50 or
30 70, a flame path is defined between surface 55 (see Figures 2 or 3) and surface 56 (see Figure 1). Surfaces 55 and 56 are shaped so that the mechanical tolerance between the mated surfaces is of the order of 0.2 to 0.4 mm. In

- 9 -

this specific example surface 55 has a diameter of 92.3 to 92.4 mm and surface 56 has a diameter of 92.0 to 92.1mm. The surfaces 55 and 56 are metallic and arranged so that, if an electrical flame occurs with the connected
5 connectors 10 and 50 or 10 and 70, gaseous material can escape along a narrow flame path defined between the surfaces 55 and 56 to release pressure from the connected connectors 10 and 50 or 10 and 70. However, because of the tight tolerances and the metallic nature of the flame path
10 surfaces 55 and 56, the gaseous material is cooled when it escapes the flame path surfaces so that the likelihood of an explosion is reduced. In this embodiment the surfaces 55 and 56 have a length of the order of 100mm.

Figure 4 (b) shows the toothed wheel 36 in greater
15 detail. Figure 4 (a) a toothed wheel 60 according to a variation of this embodiment. In this case the toothed wheel comprises an inner toothed portion for engagement with helical groove 34 and the outer periphery has a number of recesses 42a for reception of a lever (not
20 shown). The lever may be used to turn the toothed wheel 60. In this case, no toothed shaft such as toothed shaft 38 or toothed surface 42 are required.

The tooth wheel 36 and the toothed shaft 38 form a worm-drive and a rotational motion of the toothed shaft 38
25 is translated into a rotational motion of the toothed wheel 36. The rotational motion of the toothed wheel 36 is translated into a linear movement of the receptacle 50 relative to the plug 10 whereby pins such as pin 20 and sockets 52 as well as metallic flame path surfaces 55 and
30 56 move between a disengaged and an engaged condition.

In this embodiment the plug 10 also has a longitudinal keyway 62 in form of a groove that extends on the outer shell 12 across helical groove 34 in a direction

- 10 -

parallel to the imaginary axis about which the helical groove 34 is wound. The receptacles 50 and 70 have a key 64 in form of a projection that is arranged to slide in the keyway 62. The keyway 62 and the key 64 therefore
5 avoid a rotation of the plug 10 relative to the receptacle 50 or 70. The keyway 62 and the key 64 may be positioned on the connectors 10 and 50 or 70 respectively so that only connectors of a predetermined type can be connected. For example, connectors for respective applications may
10 have keyways and keys at respective positions on the connectors so that the keys and the keyways only allow connection of the respective connectors. Further, each connector may have more than one key or keyway.

Although the invention has been described with
15 reference to particular examples, it will be appreciated by those skilled in the art that the invention may be embodied in many other forms. For example, the device may comprise a plug and a receptacle and a plurality of substantially equally spaced apart drive arrangements may
20 surround the plug or the receptacle. In this case the drive arrangements may be arranged to impart driving forces at spaced apart positions. Also, the ring-like toothed wheel may have a toothed portion on one of its side surfaces arranged for engagement with a toothed shaft
25 such as shaft 38. Further, it will be understood that the device is not limited to one connector being a plug and the other connector being a receptacle. For example, both connectors may be suitable plugs or one of them may be a lug.